

MiniVac Type 812 Gas Evacuation Unit



anesthesia used in small animal surgical procedures. The MiniVac can be used in conjunction with either the Fluosorber or the F/Air filter canister. Alternatively, it can be integrated directly to the main exhaust of the building. The MiniVac can be interfaced with a wide variety of inhalation anesthetic delivery options including nose cones, induction boxes, ventilators, and stereotaxic devices. The adjustable speed allows the user to control the flow, adjusting it to the needs of their particular set up.

The MiniVac provides an ideal way to safely scavenge gas

Specifcations

Input	22 mm OD
Output	22 mm OD
Flow	~ 8 LPM to ~30 LPM
Speed	Adjustable from 1 to 10
Overall Dimensions (W x H x D)	12.5 x 9 x 12.8 cm
Power	100-240 VAC, 50-60 Hz
Regulatory	CE
Warranty	1 year

Ordering Information

Order #	Description
73-4910	MiniVac Type 812 Gas Evacuation Unit
73-4911	Adapter for Fluosorber Canister
73-4915	Adapter for F/Air Canister
34-0415	Fluosorber Canisters (up to 200 g of halogenated gas), case of 6

FEATURES

- Small footprint
- Easy to use
- Adjustable flow
- · Versatility in set up
- . Compatible with multiple filter canister options

Contact Hugo Sachs Elektronik

Germany

Gruenstrasse 1 D-79232 March-Hugstetten Germany

phone: +49 7665-92000 fax: +49 7665-920090 email: info@hugo-sachs.de web: www.hugo-sachs.de

USA

84 October Hill Road Holliston, MA 01746 United States phone: 508-893-8999 toll free: 800-272-2775

fax: 508-429-5732 email: support@hbiosci.com web: www.harvardapparatus.com